

NOVADURAN™



Properties	Test Method	Terms	Units	GF Reinforced Flame Retardant
				5010GN6-30M8X
				Low Outgas 0.30mm V-0
				GF30
Physical properties				
Density	ISO 1183	–	g/cm³	1.71
Dimensional properties				
Moulding shrinkage (2mmt)	–	MD TD	%	0.5 1.2
Rheological properties				
Melt Volume flow Rate	ISO 1133	–	cm³/10min –	18 250°C × 5kg
Mechanical properties				
Yield stress	ISO 527-1,2	–	MPa	–
Stress at break	ISO 527-1,2	–	MPa	142
Strain at break			%	3
Flexural strength	ISO 178	–	MPa	215
Flexural modulus			MPa	10,500
Charpy impact	ISO 179-1, 2	– notched	kJ/m² kJ/m²	55 10
Thermal properties				
Melting temperature	ISO 11357-3	–	°C	224
Temperature of deflection under load	ISO 75-1, 2	1.80MPa 0.45MPa	°C	>200 >200
Coefficient of Linear thermal expansion	ISO 11359-2	MD : -30~120°C MD : -30~35°C MD : 35~120°C TD : -30~120°C TD : -30~35°C TD : 35~120°C	1E-5/°C	1.9 2.0 1.9 11.1 7.1 14.1
Flammability	UL94	–	–	V-0(0.25mmt BK) V-0(0.3mmt ALL) V-0,5VA(1.5mmt ALL) V-0(3.0mmt ALL)
Electrical properties				
Volume resistivity	IEC 60093	–	Ω · m	>1E12
Surface resistivity	IEC 60093	–	Ω	>1E14
Electric strength	IEC 60243-1	1mmt 2mmt 3mmt	MV/m	24 – –
CTI	UL746A	–	–	PLC 2
RTI(Elec)	UL746B	–	–	130(0.3mmt)
RTI(Imp)	UL746B	–	–	130(0.3mmt)
RTI(Str)	UL746B	–	–	130(0.3mmt)
Molding Conditions (Standard example)				
Pre-drying Temperature	–	–	°C	120 / 140
Pre-drying Time	–	–	h	5-8 / 4-6
Cylinder temperature	–	–	°C	240-265
Mold temperature	–	–	°C	50-90
Injection speed	–	–	–	Middle-High
Injection speed	–	–	MPa	20-150
Screw speed	–	–	rpm	80-150

The values described are typical values only.